



Basic-Crete Urethanes – Epoxies – M.M.A.s

# Material Safety Data Sheet

3628 W. Holland Avenue, Fresno, CA 93722 (877) 225-2549

Date Prepared 11/28/06

<b>SECTION 1 - IDENTIFICATION</b>		HAZARD RATING	Health	2
		0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Moderate	Flammability	1
			Reactivity	0
			Personal Protection	G
IDENTITY (As Used on Label)	<b>Basic Epoxy HG Hardener</b>			
COMMON NAME	Emulsified Epoxy Resin Hardener			

SECTION II – PRODUCT COMPONENTS	CAS.#	OSHA PEL	ACGIH TLV
Water	7732-18-5	N.E. <sup>1</sup>	N.E.
Polyamine Resin	68410-23-1	N.E.	N.E.
Benzyl Alcohol	100-51-6	N.E.	N.E.
N – Butanol	71-36-3	100 ppm	20 ppm
Ethylene Glycol Monopropyl Ether	2807-30-9	N.E.	N.E.
Diglycidyl Ether Bisphenol A Epoxy Resin	25085-99-88	N.E.	N.E.
Aliphatic Epoxy Curative	Proprietary	N.E.	N.E.
Glacial Acetic Acid	64-19-7	10 ppm	10 ppm

<sup>1</sup>None Established

T.S.C.A. Status O.K. on all above components.

**\*FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300\***

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS			
Boiling Point	212F	Specific Gravity (H <sub>2</sub> O = 1)	>1
Vapor Pressure (mm Hg)	Not Known	Melting Point	N/A
Vapor Density (Air = 1)	Not Known	Evaporation rate (Butyl Acetate = 1)	Not Known
Solubility in Water	Soluble		
Appearance and Odor	Amber colored viscous liquid. Mild Odor.		

SECTION IV – FIRE AND EXPLOSION HAZARD DATA				
Flash Point	N/A	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media	Water spray, Foam, CO <sub>2</sub> , Dry Chemicals			
Special Firefighting Procedures	Wear full protective equipment including self-contained breathing apparatus.			
Unusual Fire and Explosion Hazards	Cool storage containers with water spray to prevent pressure build-up that may rupture the containers. Combustion products may be toxic.			

SECTION V – REACTIVITY DATA			
Stability	Unstable		Conditions to Avoid
	Stable	X	None Known
Incompatibility (Materials to Avoid)	None Known		
Hazardous Decomposition or Byproducts.	By Fire – Carbon monoxide, Carbon dioxide, Nitrogen oxides.		
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	None Known

<b>SECTION VI – HEALTH HAZARD DATA</b>			
Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes
Signs and Symptoms of Exposure	Irritation of skin.		
Health Hazards (Acute and Chronic)			
ACUTE – Irritation of skin and dermatitis.			
CHRONIC – Repeated overexposure will cause severe skin irritation, dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure.			
Note: Persons with lung disorders or who are sensitized should not use this product.			
Carcinogenicity	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO
Medical Conditions Generally Aggravated by Exposure			
Allergy, skin disorders.			
Emergency and First Aid Procedures			
EYES – Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.			
SKIN – Promptly wash with soap and water. Do not wash with solvents. Seek medical advice if irritation develops or persists.			
INHALATION – Move person to fresh air if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.			
INGESTION – Get medical attention immediately. Never give liquids to an unconscious or convulsing person.			
**NOTE** persons with lung disorders or who are sensitized should not use this product.			
<b>SECTION VII – CONTROL MEASURES</b>			
Respiratory Protection (Specify Type): Provide adequate exhaust ventilation; use a NIOSH approved respirator if PELs-TLVS are exceeded.			
Ventilation	Local Exhaust	If needed	Special None Known
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.	
Protective Gloves	Natural or Neoprene gloves.	Eye Protection	Splash goggles or face shield.
Other Protective Clothing or Equipment			
Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, but gloves must still be worn. An eye wash station or an adequate supply of clean water must be available at work area.			
Work/Hygienic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.			
<b>SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE</b>			
Steps to be Taken in Case Material is Released or Spilled			
Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.			
Waste Disposal Method			
Dispose in accordance with Federal, State and Local requirements.			
Precautions to be Taken in Handling and Storing			
Keep containers tightly closed when not in use.			
Other Precautions Store in an OSHA approved area for flammable materials.			
<b>Please Note</b>	“The above information is accurate to the best of our knowledge. However, since data safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Basic Polymers MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data to his particular use.”		