

3628 W. Holland Avenue, Fresno, CA 93722 (877) 225-2549

Date Prepared 11/28/06

<b>SECTION 1 - IDENTIFICATION</b>		HAZARD RATING		Health	1
		0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Moderate		Flammability	1
		IDENTITY (As Used on Label) <b>Basic Novolac Epoxy Resin</b>		Reactivity	0
		COMMON NAME Modified Epoxy Resin		Personal Protection	G
<b>SECTION II – PRODUCT COMPONENTS</b>					
	CAS.#	OSHA PEL	ACGIH TLV		
Novolac Epoxy Resin	28064-14-4	NE <sup>1</sup>	NE		
Epoxy Resin	25085-99-8	NE	NE		
Triphenyl Phosphite	101-02-2	NE	NE		
Rutile Titanium Dioxide	13463-67-7	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>		
Calcium Carbonate	1317-65-3	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>		
Aluminum Silicate	1332-58-7	15mg/m <sup>3</sup>	2mg/m <sup>3</sup>		
Barium Sulfate <sup>2</sup>	7727-43-7	10mg/m <sup>3</sup>	10mg/m <sup>3</sup>		
Inorganic Iron Oxides	1309-37-1	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>		
Chromium(III)Oxide(trivalent chromium) <sup>*3</sup>	1308-38-9	1mg/m <sup>3</sup>	0.5mg/m <sup>3</sup>		
<sup>1</sup> Not Established					
<sup>2</sup> Barium Sulfate is listed in SARA III, Part 372, Section 313					
<sup>3</sup> This product contains only 1-3ppm (0.0001%-0.0003%) leachable hexavalent chromium. Trivalent chromium is not specifically listed as a possible carcinogen. Only in Dark Green and Light Green pigmented systems.					
T.S.C.A. Status O.K.					
<b>*FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300*</b>					
<b>SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS</b>					
Boiling Point	N/A	Specific Gravity (H <sub>2</sub> O = 1)	>1		
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A		
Vapor Density (Air = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A		
Solubility in Water	Negligible				
Appearance and Odor	Pale yellow color. Mild characteristic odor.				
<b>SECTION IV – FIRE AND EXPLOSION HAZARD DATA</b>					
Flash Point	485F	Flammable Limits	LEL N/A	UEL N/A	
Extinguishing Media	Dry chemicals, carbon dioxide, foam.				
Special Firefighting Procedures	Firefighters should wear positive pressure self-contained breathing apparatus.				
Unusual Fire and Explosion Hazards	Keep vapors away from possible ignition source. Keep drums cool with a water spray to prevent excessive pressure in sealed drums which can rupture and ignite vapors. Combustion products may be toxic.				
<b>SECTION V – REACTIVITY DATA</b>					
Stability	Unstable		Conditions to Avoid		
	Stable	X	Excessive heating over long periods of time degrades resin.		
Incompatibility (Materials to Avoid)	Acids, bases, amines.				
Hazardous Decomposition or Byproducts.	By fire-carbon monoxide and phenolics.				
Hazardous Polymerization	May Occur		Conditions to Avoid		
	Will Not Occur	X	Uncontrolled reaction with amines.		

<b>SECTION VI – HEALTH HAZARD DATA</b>			
Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES
Signs and Symptoms of Exposure	Irritation of skin.		
Health Hazards (Acute and Chronic)			
ACUTE – Irritation of skin and dermatitis.			
CHRONIC – repeated overexposure will cause severe skin irritation, dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure.			
Carcinogenicity	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO
Medical Conditions Generally Aggravated by Exposure			
Allergy, skin disorders.			
Emergency and First Aid Procedures			
EYES – Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.			
SKIN – PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.			
INHALATION – Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.			
INGESTION – Get medical attention immediately. Never give liquids to an unconscious or convulsing person.			
<b>**NOTE** PERSONS WITH LUNG DISORDERS OR WHO ARE SENSITIZED SHOULD NOT USE THIS PRODUCT.</b>			
<b>SECTION VII – CONTROL MEASURES</b>			
Respiratory Protection (Specify Type): Provide adequate exhaust ventilation; use a NIOSH – approved respirator if PELs/TLVs are exceeded.			
Ventilation	Local Exhaust	If needed	Special
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator	None Known
Protective Gloves	Natural or Neoprene gloves.	Eye Protection	Splash goggles or face shield
Other Protective Clothing or Equipment			
Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams may help, but gloves must still be worn. Clean-up with soap and water. An eye wash station or an adequate supply of clean water must be available at work area.			
Work/Hygienic Practices	Enforce careful handling to prevent splashing. Wash thoroughly after use.		
<b>SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE</b>			
Steps to be Taken in Case Material is Released or Spilled			
Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.			
Waste Disposal Method			
Dispose in accordance with Federal, State and Local requirements.			
Precautions to be Taken in Handling and Storing			
Keep containers tightly closed when not in use.			
Other Precautions	None Known		
<b>Please Note</b>	“The above information is accurate to the best of our knowledge. However, since data safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Basic Polymers MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data to his particular use.”		